



# KD SideLight Frame

## Product Bulletin 08

12/16/09

A common problem with the installation of a sidelight opening in buildings is transporting the complete frame unit to the opening. Ceco Door is pleased to announce the KD SideLight Frame. This is a drywall sidelight unit that can be assembled and installed at the opening without having to weld the frame pieces together and transport them to various levels of a building. There are no more concerns of fitting the welded frame in the elevator or through doorways of a building.

The Ceco KD SideLight Frame is designed to use common hand tools for installation in a matter of minutes in a rough opening. The complete frame bundle can be carried to the specified opening and installed in a very short time, saving both labor and transportation cost.

### Sizes Available

- 4'0" x 8'0" Maximum door opening
- 8'0" x 8'0" Maximum elevation opening

### Frame

- Drywall "D" profile
- 16 gauge cold rolled or galvaneal steel
- 2" face standard – 1-1/2" and 1-3/4" available
- Sill faces available – 1-1/2" through 6"
- Jamb Depths:
  - Unequal rabbet – 4-1/2" through 8-3/4"
  - Equal rabbet – 4-7/8" through 8-3/4"
- Available factory prefinished
- Non fire rated

### Hardware

Any hardware option available in the Ceco Door price book

### Rough Opening Requirements

The rough opening height equals the finished opening height +1"  
The rough opening width equals the finished width +2"

### Tools Required for Installation

- Level
- Square
- Phillips screwdriver
- String
- Tape Measure
- Rubber Mallet
- Wood Block
- Pencil
- Frame Spacing Bar



KD SideLight Frame

The Ceco KD SideLight Frame is also available in any of the 1900 Pantone factory painted prefinish colors. Visit [www.cecodoor.com](http://www.cecodoor.com) for more information about this product and many other innovative solutions from Ceco Door.

